

Appln. No. 10/609,431  
Amendment dated January 25, 2005  
Reply to Office Action mailed October 25, 2004

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims (deleted text being struck through and added text being underlined):

1. through 6. (Cancelled)

7. (Currently Amended) [[[A]]] In combination:

a bra with a pair of shoulder straps each having a rear section; and  
a bra strap retainer comprising:

a retaining member having an elongate main portion and opposite end portions which are adapted to keep straps of a bra on a user's back in proximate relationship to one another, said retaining member engaging the body of the straps without holes, eyelets, or loops being part of the straps, each of said end portions including prongs extending outwardly therefrom and being spaced from said elongate main portion thus defining a slot therebetween, said prongs being essentially disposed in a plane with said elongate main portion, said prongs of each of said end portions extending outwardly from opposite sides of said elongate main portion, each of said prongs of a respective said end portion being curved and directed toward one of said prongs of the other said end portion, each of said prongs having an outer portion which is essentially disposed parallel to said elongate main portion, ~~said prongs and said elongate main portion being adapted to retain the straps of the bra therebetween with the straps being wound through said slots between said prongs and said elongate main portion,~~ one of said end portions being essentially C-shaped, and the other of said end portions being essentially an inverted C-shape, said retaining member having a length of approximately 1 inch and a thickness of approximately 1/8 inch with each end portion having a width of approximately 1 inch;

Appln. No. 10/609,431

Amendment dated January 25, 2005

Reply to Office Action mailed October 25, 2004

wherein each of said shoulder straps extends inward of said prongs of one of said opposite end portions with respect to the body of a wearer of said bra such that each of said end portions engages one of said shoulder straps; and

wherein each of said shoulder straps extends outward of said elongate main portion with respect to the body of the wearer of the bra such that said straps being wound through said slots between said prongs and said elongate main portion.